

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON WR 2 Hardener

Code-Nr. 103502

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

 Skin Corr. 1A
 H314

 Eye Dam. 1
 H317

 Skin Sens. 1
 H317

 Aquatic Chronic 3
 H412

Hazard Statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS05

GHS07

Signal word

Danger

Hazard Statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P301 + P330 + IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P331

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P353 water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

P338 easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

TRIETHYLENETETRAMINE, PROPOXYLATED

2.3. Other hazards

! Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Hazardous ingredients



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|------------|----------------|---|---------------|--|
| 90-72-2 | 202-013-9 | 2,4,6-Tris (dimethylaminomethyl) phenol | 1 - 3 | Acute Tox. 4, H302 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1B, H317 / Aquatic Chronic 3, H412 |
| 112-24-3 | 203-950-6 | trientine | 7 - 13 | Acute Tox. 4, H302; H312 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 Aquatic Chronic 3, H412 |
| 26950-63-0 | 500-055-5 | Triethylenetetramine, propoxylated | 13 - 30 | Acute Tox. 4, H312 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412 |
| REACH | | | | |
| CAS No | Name | | | REACH registration number |
| 90-72-2 | 2,4,6-Tris (di | methylaminomethyl) phenol | | 01-2119560597-27 |
| 112-24-3 | trientine | | | not subject to registration |
| 26950-63-0 | Triethylenete | tramine, propoxylated | | not subject to registrattion |

! SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

Seek medical treatment immediately.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Seek medical treatment immediately.

In case of skin contact, rinse with water for at least 10 minutes.

! In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth thoroughly with water.

Give plenty of water to drink in small sips.

4.2. Most important symptoms and effects, both acute and delayed

! Physician's information / possible symptoms

vomiting

Skin burns

Nausea

! Physician's information / possible dangers

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Collect contaminated firefighting water separately, must not be discharged into the drains.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

! Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Store closed container at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Storage temperature between 2°C to 40°C

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL-/PNEC-values

DNEL worker

| CAS No | Substance name | Value | Code | Remark |
|----------|---|------------------------|--|--------|
| 112-24-3 | trientine | 1 mg/kg | DNEL acute dermal, short-term (local) | |
| | | 8 mg/kg bw/day | DNEL acute dermal, short-term (systemic) | |
| | | 0,41 mg/kg bw/day | DNEL long-term oral (repeated) | |
| | | 0,028 mg/ kg bw/day | DNEL long-term dermal (local) | |
| | | 20 mg/kg | DNEL short-term oral (acute) | |
| | | 5380 mg/m3 | DNEL acute inhalative (systemic) | |
| | | 1 mg/m3 | DNEL long-term inhalative (systemic) | |
| | | 0,57 mg/kg bw/day | DNEL long-term dermal (systemic) | |
| 90-72-2 | 2,4,6-Tris (dimethylaminomethyl) phenol | 0,31 mg/m3 | DNEL long-term inhalative (systemic) | |
| PNEC | | | | |
| CAS No | Substance name | Value | Code | Remark |
| 112-24-3 | trientine | 0,19 mg/l | PNEC aquatic, freshwater | |
| | | 19,2 mg/kg | PNEC sediment, marine water | |
| | | 95,9 mg/kg | PNEC sediment, freshwater | |
| | | | | |



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| DNEL-/PNE | DNEL-/PNEC-values (continued) | | | | |
|-----------|---|-------------|----------------------------------|------------|--|
| CAS No | Substance name | Value | Code | Remark | |
| | | 0,038 mg/l | PNEC aquatic, marine water | | |
| | | 4,25 mg/l | PNEC sewage treatment plant (STF | ') | |
| 90-72-2 | 2,4,6-Tris (dimethylaminomethyl) phenol | 0,0084 mg/l | PNEC aquatic, marine water | | |
| | | 0,2 mg/l | PNEC sewage treatment plant (STF | ?) | |
| | | 0,084 mg/l | PNEC aquatic, freshwater | | |

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

! Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, filter AX

! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min:60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

pasty green hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|---------------|---------------|-------------|----|--------|--------------|
| pH value | 11-12 | 20 °C | | | 1:1 in water |
| boiling point | > 200 °C | | | | |
| melting point | not determine | d | | | |



No. 1907/2006 (REACH) Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| | Value | Temperature | at | Method | Remark |
|---|----------------|-------------|----|-----------|----------------------------------|
| Flash point | > 100 °C | | | DIN 51758 | Pensky-Martens Closed Cup |
| Vapourisation rate | not determined | | | | |
| Flammable (solid) | not applicable | | | | |
| Flammability (gas) | not applicable | | | | |
| Ignition temperature | > 200 °C | | | | |
| Self ignition temperature | | | | | The product is no self-igniting. |
| Lower explosion limit | not determined | | | | |
| Upper explosion limit | not determined | | | | |
| Vapour pressure | not determined | | | | |
| Relative density | ca. 1,6 g/ml | 23 °C | | | |
| Vapour density | not determined | | | | |
| Solubility in water | | 20 °C | | | soluble |
| Solubility/other | not determined | | | | |
| Partition coefficient n- octanol/water (log P O/W) | not determined | | | | |
| Decomposition temperature | > 200 °C | | | | |
| Viscosity kinematic | not determined | 40 °C | | | |
| Viscosity dynamic | not determined | | | | |
| Oxidising properties No information available. | | | | | |
| Explosive properties No information available. | | | | | |
| 9.2. Other information No information available. | | | | | |

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials Substances to avoid

Alkali (lye), concentrated Acid, concentrated Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide. Nitrous oxides (NOx) Toxic gases/vapours

Metaloxides

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

| • | | | | |
|-----------------------|------------------|------------|---|------------|
| | Value/Validation | Species | Method | Remark |
| LD50 acute oral | > 5000 mg/kg | | | ATE |
| LD50 acute dermal | > 3000 mg/kg | | | ATE |
| LC50 acute inhalation | > 50 mg/l () | | | ATE |
| Skin irritation | corrosive | rabbit | OECD 404 Acute Dermal Irritation / Corrosion | |
| Eye irritation | corrosive | rabbit eye | OECD 405 Acute Eye Irritation/ Corrosion | |
| Skin sensitization | sensitizing | Guinea pig | OECD 406 Skin Sensitization | |
| Subacute Toxicity - 0 | Carcinogenicity | | | |
| | Value | Species | Method | Validation |

Chronic Toxicity NOAEL 50 mg/kg (90 d) OECD 408 -

Repeated Dose 90-Day Oral Toxicity Study in Rodents

CAS: 112-24-3



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| | Value | Species | Method | Validation |
|---------------------------|---|---------|---|---|
| Mutagenicity | CAS: 112-24-3 | | OECD 482 Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells in vitro | No experimental information on genotoxicity in vitro available. |
| Reproduction- Toxicity | NOEL Experimental value CAS: 90-72-2 | | OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test | No indications of toxic effects were observed in reproduction studies in animals. |
| Carcinogenicity | Carcinogenicity Studies / 3d/we CAS: 90-72-2 | eek | OECD 451 Carcinogenicity Studies | No indications of carcinogenic effects are available from long-term trials. |

Experiences made from practice

Corrosive effect on skin and mucous membrane.

Sensitization through skin contact possible.

Causes corrosions.

Risk of strong eye injuries.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

| Value | Species | Method | Validation | |
|------------------------|---|--|---|--|
| LC50 330 mg/l (96 h) | Fish | EPA OPPTS EPA OTS 797. 1400 | CAS: 112-24-3 | |
| EC50 31,1 mg/l (48 h) | Daphnia magna | EU EC C.2 Acute Toxicity for Daphnia | CAS: 112-24-3 | |
| ErC50 20 mg/l (72 h) | Green algae | OECD 201 | CAS: 112-24-3 | |
| EC50 800 mg/l (30 min) | Leuciscus idus | | CAS: 112-24-3 | |
| | Value LC50 330 mg/l (96 h) EC50 31,1 mg/l (48 h) ErC50 20 mg/l (72 h) | Value Species LC50 330 mg/l (96 h) Fish EC50 31,1 mg/l (48 h) Daphnia magna ErC50 20 mg/l (72 h) Green algae | Value Species Method LC50 330 mg/l (96 h) Fish EPA OPPTS EPA OTS 797. 1400 EC50 31,1 mg/l (48 h) Daphnia magna EU EC C.2 Acute Toxicity for Daphnia ErC50 20 mg/l (72 h) Green algae OECD 201 | Value Species Method Validation LC50 330 mg/l (96 h) Fish EPA OPPTS EPA OTS 797. 1400 CAS: 112-24-3 EC50 31,1 mg/l (48 h) Daphnia magna EU EC C.2 Acute Toxicity for Daphnia CAS: 112-24-3 ErC50 20 mg/l (72 h) Green algae OECD 201 CAS: 112-24-3 |



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| 12.2. Persistence | and degradability Elimination rate | Method of analysis | Method | Validation |
|-------------------|------------------------------------|--------------------|------------|----------------|
| Biological | 0 % (162 d) | | OECD 301 D | not degradable |
| degradability | CAS: 112-24-3 | | | |
| Degradability | 4 % (28 d) | | OECD 301 D | not degradable |
| | CAS: 90-72-2 | | | |

12.3. Bioaccumulative potential

Slight bioaccumulation potential.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

07 02 04*

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

Dispose of according to the local waste regulations.

! General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA-DGR |
|-------------------------------|--|---|---|
| 14.1. UN number | 2735 | 2735 | 2735 |
| 14.2. UN proper shipping name | AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMIN E, PROPOXYLATED) | AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, PROPOXYLATED) | Amines, liquid, corrosive, n.o. s. (TRIETHYLENETETRAMINE, PROPOXYLATED) |



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

| | ADR/RID | IMDG | IATA-DGR |
|----------------------------------|---------|------|----------|
| 14.3. Transport hazard class(es) | 8 | 8 | 8 |
| 14.4. Packing group | II | II | II |
| 14.5. Environmental hazards | No | No | No |

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 8 tunnel restriction code E Special provisions 274 Classification code C7

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

| H302 Harmiui II Swallowed | H302 | Harmful if swallowed. |
|---------------------------|------|-----------------------|
|---------------------------|------|-----------------------|

H302: -?-

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 10.07.2018 (GB) Version 8.5

WEICON WR 2 Hardener

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.