

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Flex 310 M Super-Tack

Code-Nr. 136500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

1-Component Adhesives and Sealants, permanently elastic

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

# **Additional hints**

This mixture is not classified as hazardous according to Regulation (EC) 1272/2008 [GHS].

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]

No information available.

#### 2.3. Other hazards



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# Information pertaining to special dangers for human and environment

Although this product is not subject to reporting requirements for hazardous products, we recommend compliance with the safety recommendations.

# Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# ! SECTION 3: Composition/ information on ingredients

#### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Sealant

#### ! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
2768-02-7	220-449-8	trimethoxyvinylsilane	1 < 3	Flam. Liq. 3, H226 / Acute Tox. 4;, H332
REACH				
CAS No	Name			REACH registration number
2768-02-7	trimethoxyvin	ylsilane		01-2119513215-52

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

Remove moisted clothing immediately.

# In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

### In case of skin contact

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

# In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

# In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

Rinse out mouth thoroughly with water.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam

ABC powder

Carbon dioxide

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen gases (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

# Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

# 6.3. Methods and material for containment and cleaning up

Clean with cleaning agents that do not contain solvents.

Take up mechanically and send for disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

# ! SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Take the usual precautions when handling with chemicals.

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# Hygiene measures

At work do not eat, drink and smoke. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

# Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

# 7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep in closed original container.

#### Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

# ! Further information on storage conditions

Protect from atmospheric moisture and water

Protect from heat.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

Recommended storage temperature: room temperature.

# 7.3. Specific end use(s)

# Recommendation(s) for intended use

See section 1.2

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

**DNEL-/PNEC-values** 

**DNEL** worker

CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	4,9 mg/m3	DNEL long-term inhalative (systemic)	
		0,69 mg/kg bw/day	DNEL long-term dermal (systemic)	
DNEL Consu	umer			
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	0,3 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
		93,4 mg/m3	DNEL acute inhalative (systemic)	
		1,04 mg/m3	DNEL long-term inhalative (systemic)	
		26,9 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
PNEC				
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	0,12 mg/kg dw	PNEC sediment, marine water	
		1,24 mg/kg dw	PNEC sediment, freshwater	



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

DNEL-/PNEC-values (continued)					
CAS No	Substance name	Value	Code	Remark	
		3,4 mg/l	PNEC aquatic, intermittent release		
		0,034 mg/l	PNEC aquatic, marine water		
		0,34 mg/l	PNEC aquatic, freshwater		

#### **Additional advice**

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

# Respiratory protection

If ventilation insufficient, wear respiratory protection.

#### **Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

## Eye protection

tightly fitting goggles

### Other protection measures

protective clothing

# Appropriate engineering controls

Sufficient ventilation and exhaustion.

# ! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourpastyvarious, depending on colorationcharacteristic

# Odour threshold not determined

# Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	not applicable				
Vapourisation rate	not determined				
Flammable (solid)	no				
Flammability (gas)	not determined				
Ignition temperature	not applicable				



No. 1907/2006 (REACH) Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

	Value	Temperature	at	Method	Remark
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	1,6 g/cm3	20 °C			
Bulk density	1600 kg/m3				Absolute Dichte
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other					soluble in most of organic solvents
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Oxidising properties no					
Explosive properties no					
<b>9.2. Other information</b> No information available.					

# ! SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information available.

# 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

No information available.

# 10.4. Conditions to avoid

Keep away from heat.

# 10.5. Incompatible materials

No information available.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# 10.6. Hazardous decomposition products

Nitrous gases

Carbon monoxide and carbon dioxide.

Metaloxides

# Thermal decomposition

Remark No decomposition if used as directed.

# ! SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	7120 mg/kg	rat	OECD 401	CAS: 2768-02-7
LD50 acute dermal	3,36 mg/kg	rabbit	OECD 402	CAS: 2768-02-7
LC50 acute inhalation	16,8 mg/l (4 h)	rat	OECD 403	CAS: 2768-02-7
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity						
	Value	Species	Method	Validation		
Chronic Toxicity				-		
Mutagenicity				No experimental information on genotoxicity in vitro available.		
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.		
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.		

# **Experiences made from practice**

According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

Frequent persistent contact with the skin may cause skin irritation.

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# ! SECTION 12: Ecological information

#### 12.1. Toxicity

#### **Ecotoxicological effects**

J	Value	Species	Method	Validation	
Fish	LC50 191 mg/l (96 h)	Oncorhynchus n	nykiss	CAS: 2768-02-7	
Daphnia	EC50 168,7 mg/l (48 h)	Daphnia magna	EU Methode C.	2 CAS: 2768-02-7	
Algae	EC50 210 mg/l (7 d)	Pseudokirchneri subcapitata	ella EPA 67014-73-	0 CAS: 2768-02-7	
12.2. Persiste	ence and degradability Elimination rate	Method of analysis	Method	Validation	
Biological degradability	51 % (28 d)		OECD 301 F	not readily degradable	

# 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

# **General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Waste code No.

Name of waste

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

15 01 02 plastic packaging

#### Recommendations for the product

Remove in accordance with local official regulations.

# Recommendations for packaging

Dispose of according to the local waste regulations.

### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 05.01.2018 (GB) Version 8.7

Flex 310 M Super-Tack

# ! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazard	s -	-	-

#### 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

# ! Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

# ! SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

! VOC standard

 VOC content
 2,61 %

 VOC value
 41,78 g/L

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

# **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.6

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.