

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Flex 310 M HT 200 Code-Nr. 136550

00001....

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)

1-Component Adhesives and Sealants, permanently elastic

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

### **Additional hints**

This mixture is not classified as hazardous according to Regulation (EC) 1272/2008 [GHS].

### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]

## Special rules for supplemental label elements for certain mixtures

Safety data sheet available on request.

### 2.3. Other hazards



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

### Information pertaining to special dangers for human and environment

Although this product is not subject to reporting requirements for hazardous products, we recommend compliance with the safety recommendations.

## Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

not applicable

### 3.2. Mixtures

### Description

Sealant

### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
2768-02-7	220-449-8	trimethoxyvinylsilane	< 2	Flam. Liq. 3, H226 / Acute Tox. 4;, H332
REACH				
CAS No	Name			REACH registration number
2768-02-7	trimethoxyvinylsilane			01-2119513215-52

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

Remove moisted clothing immediately.

### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

### In case of skin contact

Dab affected skin part with a cotton ball or cellulose and wash it afterwards with plenty of water and a mild cleaner.

### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

## In case of ingestion

Call for a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Methanol

### 5.3. Advice for firefighters

## Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

### **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

### 6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Take the usual precautions when handling with chemicals.

### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

### Hygiene measures

At work do not eat, drink and smoke.

Keep away from food and drink.

Wash hands before breaks and after work.

## Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in closed original container.

Prevent penetration into the ground.



Remark

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

## Advice on storage compatibility

Do not store with acids.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

## Further information on storage conditions

Store closed container at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

Protect from heat/overheating.

## 7.3. Specific end use(s)

## Recommendation(s) for intended use

See section 1.2

## **SECTION 8: Exposure controls/personal protection**

Substance name

# 8.1. Control parameters DNEL-/PNEC-values

DNEL worker

**CAS No** 

2768-02-7	trimethoxyvinylsilane	4,9 mg/m3	DNEL long-term inhalative (systemic)	
		0,69 mg/kg bw/day	DNEL long-term dermal (systemic)	
DNEL Consu	umer			
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	0,3 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
		93,4 mg/m3	DNEL acute inhalative (systemic)	
		1,04 mg/m3	DNEL long-term inhalative (systemic)	
		26,9 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
PNEC				
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	0,12 mg/kg dw	PNEC sediment, marine water	
		1,24 mg/kg dw	PNEC sediment, freshwater	
		3,4 mg/l	PNEC aquatic, intermittent release	
		0,034 mg/l	PNEC aquatic, marine water	
		0,34 mg/l	PNEC aquatic, freshwater	

Code

Value

### **Additional advice**

The statutory local and national regulations have to be observed.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

# 8.2. Exposure controls Respiratory protection

Not required

### **Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

### Eye protection

tightly fitting goggles

### Other protection measures

protective clothing

## Appropriate engineering controls

Sufficient ventilation and exhaustion.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance<br/>pastyColour<br/>greyOdour<br/>characteristic

Odour threshold not determined

## Important health, safety and environmental information

Important health, safety and environmental information					
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
melting point	not applicable				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	420 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 100 hPa				
Relative density	1,41 g/cm3	20 °C			



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

	Value	Temperature	at	Method	Remark
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Oxidising properties No information available.					
Explosive properties No information available.					
<b>9.2. Other information</b> No information available.					

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No information available.

## 10.2. Chemical stability

No information available.

## 10.3. Possibility of hazardous reactions

Reactions with acids.

Reactions with strong oxidising agents.

## 10.4. Conditions to avoid

Keep away from heat.

Liberates methanol in contact with water resp. moisture.

## 10.5. Incompatible materials

### Substances to avoid

Acid

Oxidising agent, strong

## 10.6. Hazardous decomposition products

May form metahanol in contact with water / moisture.

Carbon monoxide and carbon dioxide.

## Thermal decomposition

Remark No decomposition if used as directed.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LC50 acute inhalation	918 mg/l ()			ATE
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

## **Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

### **Experiences made from practice**

According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

Frequent persistent contact with the skin may cause skin irritation.

### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

No information available.

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

### 12.6. Other adverse effects

### **General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods Waste code No. Name of waste 08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 08 04 11\* adhesive and sealant sludges containing organic solvents or other hazardous 08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11 15 01 02 plastic packaging 15 01 10\* packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

### Recommendations for the product

Remove in accordance with local official regulations.

### Recommendations for packaging

Dispose of according to the local waste regulations.

### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	<b>3</b> -	-	-

### 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

### Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 03.08.2016 (GB) Version 8.5

Flex 310 M HT 200

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

 VOC content
 0,02 %

 VOC value
 0,3 g/L

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.